

EN 14800 GAS HOSES
“GT COOK”

FEATURES AND PARTICULARS

GT COOK

EN 14800 flexible gas hose is built with corrugated hose in stainless steel, reinforced with braid in stainless steel and outer is protected with PVC yellow cover.

This hose is used to connect gas valve to kitchen plane in respect to normative EN 14800. Connection fittings are in stainless steel.

The yellow protective PVC cover, protect the hose from heat (120°C) and from acids attack (pitting) typical of clean products used in domestic ambient. This cover protect the hose also from electrostatic currents and from crashes, that it can to damaged the hose. Hose's thickness is > 0,13 mm.

The standard lengths of these hoses are 500 – 750 – 1000 -1250 – 1500 – 2000 mm and can be supply also with single cellophane package with NBR rubber washers, with installation's instructions.



EN 14800 GAS HOSES "GT COOK"

DN	Fittings	Lengths	Code
12	1/2''F - 1/2''F	500 mm	EG15FF-A
12	1/2''F - 1/2''F	750 mm	EG15FF-B
12	1/2''F - 1/2''F	1000 mm	EG15FF-C
12	1/2''F - 1/2''F	1250 mm	EG15FF-D
12	1/2''F - 1/2''F	1500 mm	EG15FF-E
12	1/2''F - 1/2''F	2000 mm	EG15FF-F

12	1/2''M - 1/2''F	500 mm	EG15MF-A
12	1/2''M - 1/2''F	750 mm	EG15MF-B
12	1/2''M - 1/2''F	1000 mm	EG15MF-C
12	1/2''M - 1/2''F	1250 mm	EG15MF-D
12	1/2''M - 1/2''F	1500 mm	EG15MF-E
12	1/2''M - 1/2''F	2000 mm	EG15MF-F