

EXTENSIBLE HOSES
“GT GAS”

EXTENSIBLES "GT GAS"	
Sheet	A

FEATURES AND PARTICULARS

GT GAS

Flexible and extensible hose built in stainless steel 316L with yellow protective cover in poliofiline to normative UNI-CIG 9891/1998 and UNI-CIG 7129 and UNI-CIG 7131.

This hose is used to connect gas valve to cook plane to normative UNI-CIG 9891/1998, is built in stainless steel 316L with fittings in stainless steel 304.

The yellow protective cover, protect the hose from heat (120°C) and from acids attack (pitting) typical of clean products used in domestic ambient. This cover protect the hose also from electrostatic currents and from crashes, that it can to damaged the hose. Hose's thickness is > 0,21 mm.

These hoses with lengths 500÷1000, 750÷1500 and 1000÷2000 it can be supply also with single cellophane package with aluminum washers, with installation's instructions.



EXTENSIBLE HOSES "GT GAS"

DN (mm)	Fittings	Length from ÷ to (mm)	Code
15	1/2"F - 1/2"F	500 ÷ 1000	EG15FF-5
15	1/2"F - 1/2"F	750 ÷ 1500	EG15FF-6
15	1/2"F - 1/2"F	1000 ÷ 2000	EG15FF-7
15	1/2"M - 1/2"F	500 ÷ 1000	EG15MF-5
15	1/2"M - 1/2"F	750 ÷ 1500	EG15MF-6
15	1/2"M - 1/2"F	1000 ÷ 2000	EG15MF-7
15	1/2"M - 1/2"F	75 ÷ 125	EG15MF-1
15	1/2"M - 1/2"F	100 ÷ 200	EG15MF-2
15	1/2"M - 1/2"F	200 ÷ 400	EG15MF-3
15	1/2"M - 3/4"F	75 ÷ 125	EG15M20F-1
15	1/2"M - 3/4"F	100 ÷ 200	EG15M20F-2
15	1/2"M - 3/4"F	200 ÷ 400	EG15M20F-3
20	3/4"M - 3/4"F	80 ÷ 125	EG20MF-1
20	3/4"M - 3/4"F	110 ÷ 200	EG20MF-2
20	3/4"M - 3/4"F	200 ÷ 400	EG20MF-3
25	1"M - 1"F	80 ÷ 125	EG25MF-1
25	1"M - 1"F	110 ÷ 200	EG25MF-2
25	1"M - 1"F	200 ÷ 400	EG25MF-3
32	1"1/4M - 1"1/4F	120 ÷ 200	EG32MF-2
32	1"1/4M - 1"1/4F	210 ÷ 400	EG32MF-3
40	1"1/2M - 1"1/2F	130 ÷ 200	EG40MF-2
40	1"1/2M - 1"1/2F	220 ÷ 400	EG40MF-3
50	2"M - 2"F	150 ÷ 230	EG50MF-2
50	2"M - 2"F	230 ÷ 400	EG50MF-3