

EXTENSIBLE HOSES
“GT WATER”

EXTENSIBLES "GT WATER"	
Sheet	A

FEATURES AND PARTICULARS

GT WATER

Flexible and extensible hose built in stainless steel 304. This hose is used to connect sanitary water plants heating water plants and to food grade usage plants. Floating female fitting have internal part built in stainless steel 304 and the floating nut is built in nickel-plate brass with fillet connection UNI ISO 228/1. Fixed male fitting is built in stainless steel 304 with fillet connection UNI ISO 7/1; in this conditions the fluid is always in contact with stainless steel!!

Hose's thickness is > 0,21 mm.

Max working pressure to 20°C for following diameters is:

DN	Bar
15	10
20	8
25	6
32	2,5
40	2
50	1,6



N.B.: To 100°C the design pressure it be reduced of 20%

EXTENSIBLE HOSES "GT WATER"

DN (mm)	Fittings	Lengths from ÷ to (mm)	Code
15	1/2"M - 1/2"F	70 ÷ 125	EW15MF-1
15	1/2"M - 1/2"F	100 ÷ 200	EW15MF-2
15	1/2"M - 1/2"F	200 ÷ 400	EW15MF-3
15	1/2"M - 3/4"F	70 ÷ 125	EW15M20F-1
15	1/2"M - 3/4"F	100 ÷ 200	EW15M20F-2
15	1/2"M - 3/4"F	200 ÷ 400	EW15M20F-3
20	3/4"M - 3/4"F	75 ÷ 125	EW20MF-1
20	3/4"M - 3/4"F	110 ÷ 200	EW20MF-2
20	3/4"M - 3/4"F	200 ÷ 400	EW20MF-3
25	1"M - 1"F	80 ÷ 125	EW25MF-1
25	1"M - 1"F	110 ÷ 200	EW25MF-2
25	1"M - 1"F	200 ÷ 400	EW25MF-3
32	1"1/4M - 1"1/4F	120 ÷ 200	EW32MF-2
32	1"1/4M - 1"1/4F	200 ÷ 400	EW32MF-3
40	1"1/2M - 1"1/2F	125 ÷ 200	EW40MF-2
40	1"1/2M - 1"1/2F	210 ÷ 400	EW40MF-3
50	2"M - 2"F	130 ÷ 200	EW50MF-2
50	2"M - 2"F	220 ÷ 400	EW50MF-3